


# 24" Military Full IP 67 Display

**MODEL: SD-24RMLD**




## FEATURES



**Size / Type**  
24"



**Brightness**  
1000 nits



**Contrast**  
5000: 1 (typ.)



**Max. Colors**  
16.7 M



**Viewing Angle**  
-89~89(H); -89~89(V);



**Resolution**  
1920 x 1080 @ 60Hz

## SPECIFICATION

PANEL SPECIFICATION	
Size / Type	24" LCD (LED backlight)
Resolution	1920 x 1080 @ 60Hz
Active Area (mm)	531.36 (H) x 289.89 (V)
Contrast Ratio	5,000 : 1 (typ.)
Max. Colors	16.7M colors
Brightness	1000 nits
Viewing Angle	-89 ~ 89 (H); -89 ~ 89 (V)
Touch Screen	P-cap multi touch screen
Pixel Pitch (mm)	0.27675 (H)x 0.27675 (V)
ENVIRONMENT TOLERANCE	
Operating Temperature	-20 deg. C to 60 deg. C
Storage Temperature	-30 deg. C to 80 deg. C
Humidity	10 to 95% (Non Condensing)
Shock	MIL-STD-810G Method 516.6
Vibration	MIL-STD-810G Method 514.6C-3
Humidity	MIL-STD-810G Method 507.5-7
High Temperature	MIL-STD-810G Method 501.5-II
Low Temperature	MIL-STD-810G Method 502.5
IP Level	Full IP67
EMI Compliance	MIL -STD-461F, CE101, CE102, RE101, RE102, CS101, CS114, CS115, CS116, RS101, RS103
FUNCTION KEY	
Power Button	1 x Power Button
Up / Down Arrow	Brightness Control Buttons
Other Buttons	Reserved for user definition
LED Indicators	1 x Power On/Off
INPUT / OUTPUT	
Back Side I/O (D38999/24WH53SN)	1 x PAL / NTSC Input , 1 x DVI Input, 1 x VGA Input
Back Side I/O ( D38999/26WD5PN)	1 x DC 16~32V Input
Front Side I/O (optional)	2 x IP67 Type A USB 2.0 connectors (Optional)

DIMENSIONS	
Dimensions	590 (W) x 400(H) x 72.5 (D) mm
Weight	14 KG

ORDER OPTIONS	
Optical Bonding	Optical bonding between panel and glass (or touch screen)
Table Stand	Table Stand for optional

## DRAWINGS

